DPM 6098

2nd Copy

MATERIAL SAFETY DATA SHEET

WEC'DDEC 21 1987

PRODUCT NAME 3-36 (Aerosol) #3004, 3005				# MSDS003004		
MANUFACTURED BY: CRC CHEMICALS			Phone (215) 674-4300			
885 LOUIS DRIVE, WARMINSTER, PA.						
1. INGREDIENTS	CAS#	ACGIH TLV	OSHA PEL	Other Limits	%	
Petroleum Distillate	64742-47-8	NA	NA	200ppm	42	
1,1,1 Trichloroethane	71-55-6	350 ·	350		29	
*Inhibited paraffinic oi	NA		As mist		25	
Carbon Dioxide	124-38-9	5000	5000		4	
*The oil and additives as	re not hazardous ac	cording t	o OSHA s	tandards	.	
The carbon dioxide is the	e propellent for t	his conta	iner. I	ressure	=	
85 psig at 70°F.	·					
					-	
	·					
2. PHYSICAL DATA (Without	ut Propellent)					
pecific Gravity 0.932	Vapor Pressure 6.2 mm	9	6 Volatile	76		
Boiling Point 220 F (Initial)	Evaporation Rate NA					
Freezing Point NA	Vapor Density Heavier	than air	• ————————————————————————————————————			
Appearance and Odor Blue 1	iquid, pleasant odo	r		******		
		r				
		r				
Solubility <u>Megligible in t</u>	water.	r				
Solubility Negligible in 1	water.		ammable Lir	mits NA		
3. FIRE AND EXPLOSION DAT Flashpoint 170°F Method COC Extinguishing Media Foam, Fog	Water. A Dry Chemical, CO.	FI	L	UEL		
3. FIRE AND EXPLOSION DAT Flashpoint 170°F Method COC Extinguishing Media Foam, Fog	water.	FI	L	UEL		
3. FIRE AND EXPLOSION DAT Flashpoint 170°F Method COC Extinguishing Media Foam, Fog	Water. A Dry Chemical, CO.	FI	L	UEL		
3. FIRE AND EXPLOSION DAT Flashpoint 170°F Method COC Extinguishing Media Foam, Fog	water. A Pry Chemical, CO2 tainers may explode	FI	L	UEL		
3. FIRE AND EXPLOSION DATE Flashpoint 170°F Method COC Extinguishing Media Foam, Fogunusual Hazards Aerosol con	water. A Pry Chemical, CO2 tainers may explode	FI	L	UEL		
3. FIRE AND EXPLOSION DATE Flashpoint 170°F Method COC Extinguishing Media Foam, Formula Unusual Hazards Aerosol con 4. REACTIVITY AND STABILITY	water. A Dry Chemical, CO2 tainers may explode	when hea	ted above	UEL ve 130 [°] F.	mono	
3. FIRE AND EXPLOSION DATE Flashpoint 170°F Method COC Extinguishing Media Foam, Foque Unusual Hazards Aerosol con 4. REACTIVITY AND STABILITY Stability Stable	water. A Dry Chemical. CO2 tainers may explode Y hermalHydrogen ch	when hea	ted above	UEL ve 130 ⁰ F.	mono	
3. FIRE AND EXPLOSION DATE Flashpoint 170°F Method COC Extinguishing Media Foam, Foque Unusual Hazards Aerosol con 4. REACTIVITY AND STABILITY Stability Stable Hazardous decomposition products T	water. A Dry Chemical. CO2 tainers may explode Y hermalHydrogen ch	when hea	ted above	UEL ve 130 [°] F.	mono	
3. FIRE AND EXPLOSION DATE Flashpoint 170°F Method COC Extinguishing Media Foam, Foque Unusual Hazards Aerosol con 4. REACTIVITY AND STABILITY Stability Stable Hazardous decomposition products T	water. A Dry Chemical, CO tainers may explode Y hermalHydrogen ch izers	when hea	ted above	UEL ve 130 [°] F.	mono	
3. FIRE AND EXPLOSION DATE Flashpoint 170°F Method COC Extinguishing Media Foam. For Unusual Hazards Aerosol constability Stable Hazardous decomposition products materials to avoid Strong oxid	water. A Dry Chemical, CO tainers may explode Y hermalHydrogen ch izers	when head	ted above	ve 130 [°] F. , carbon y phoseer	mono	
3. FIRE AND EXPLOSION DATE Flashpoint 170°F Method COC Extinguishing Media Foam, Foquency Unusual Hazards Aerosol con 4. REACTIVITY AND STABILITY Stability Stable Hazardous decomposition products materials to avoid Strong oxid Strong oxid Strong oxid Ventilation Mechanical vent	Mater. A Dry Chemical, CO ₂ tainers may explode Y hermalHydrogen ch izers	when head and and onc. is at	ted above the possibly	ve 130°F.	mono:	
3. FIRE AND EXPLOSION DATE Flashpoint 170°F Method COC Extinguishing Media Foam, Foque Unusual Hazards Aerosol con 4. REACTIVITY AND STABILITY Stability Stable Hazardous decomposition products materials to avoid Strong oxid Strong oxid Strong oxid ventilation Mechanical vent	water. A Dry Chemical. CO2 tainers may explode Y hermalHydrogen chizers ON ilation if vapor contractions apparatus	when head and and onc. is at	ted above the possibly cove TLV	ve 130°F.	mono:	
3. FIRE AND EXPLOSION DATE Flashpoint 170°F Method COC Extinguishing Media Foam, Foquenusual Hazards Aerosol consultation Stability Stable Hazardous decomposition products The Materials to avoid Strong oxid Strong oxid Strong oxid Strong oxid Methods Strong oxid Strong	water. A Dry Chemical. CO2 tainers may explode Y hermalHydrogen chizers ON ilation if vapor contractions apparatus	when head and and if vapor	ted above the possibly cove TLV	ve 130°F.	mono:	

6. HEALTH HAZARD DATA					
Primary Routes of Entry Skin & Inha	lation				
Signs and Symptoms of Exposure					
. Acute Overexposure Inhalation -	Headache	, dizzi	ness & na	usea - may	v also have
some anesthetic effect. Eye	s - burnir	ng and	irritatio	n. Skin	causes
drying and defatting.			· · · · · · · · · · · · · · · · ·		
2. Chronic Overexposure Dermatiti	s.				
Medical Conditions Generally Aggravated by E	Exposure Des	athina	condition		
Viedical Conditions Constany Mag. 400000 47	ble	acming	COHOLLIC	113	
Chemical Listed as Carcinogen or Potential Carcinogen	National Toxicology Program	Yes 🗆 NoXCX	IARC Monographs	Yes □ No 汉 文	OSHA Yes I
Emergency and First Aid Procedures (Tf	symptoms r	ersist	call a p	hvsician)	
I Inhalation Remove to fresh air					necessary.
2. Eyes Flush with large amou					
3. Skin Wash with soap and wa					
1. Ingestion Do not induce vomit		a như	gician		
7. SPILL OR LEAK PROCEDURES	Ind - Car	L A MUY	SILIANA		
Precautions to be taken in Store in a cool Handling and Storage	, dry area	١.			
Steps to be taken in case Materials is released or spilled Ventilate a	rea, absor	b with	inert ma	terial and	i place
in a closed container.					
11. 4 010004 0011011					
	·				
Waste Disposal Partially used o	or full ae	cosols	are Hazar	dous Waste	e if
discarded. Dispose of in co	nformance	with F			
discarded. Dispose of in co 8. SPECIAL PRECAUTIONS AND L	onformance JSE DIRECT	with F	ederal. S	tate and 1	
discarded. Dispose of in co 8. SPECIAL PRECAUTIONS AND L Aerosols may explode if cont	onformance USE DIRECT	with F IONS neated	ederal. S above 130	tate and o	Cocal recula
discarded. Dispose of in co 8. SPECIAL PRECAUTIONS AND L	onformance USE DIRECT	with F IONS neated	ederal. S above 130	tate and o	Cocal recula
discarded. Dispose of in co 8. SPECIAL PRECAUTIONS AND L Aerosols may explode if cont	onformance USE DIRECT	with F IONS neated	ederal. S above 130	tate and o	Cocal recula
discarded. Dispose of in co 8. SPECIAL PRECAUTIONS AND L Aerosols may explode if cont	onformance USE DIRECT	with F IONS neated	ederal. S above 130	tate and o	Cocal recula
discarded. Dispose of in co 8. SPECIAL PRECAUTIONS AND L Aerosols may explode if cont	onformance USE DIRECT	with F IONS neated	ederal. S above 130	tate and o	Cocal recula
discarded. Dispose of in co 8. SPECIAL PRECAUTIONS AND L Aerosols may explode if cont	onformance USE DIRECT	with F IONS neated	ederal. S above 130	tate and o	Cocal recula
discarded. Dispose of in co 8. SPECIAL PRECAUTIONS AND L Aerosols may explode if cont	onformance USE DIRECT	with F IONS neated	ederal. S above 130	tate and o	Cocal recula
discarded. Dispose of in co 8. SPECIAL PRECAUTIONS AND L Aerosols may explode if cont	onformance USE DIRECT	with F IONS neated	ederal. S above 130	tate and o	Cocal recula